



福建南环检测技术有限公司

Fujian Nanhuan Detection Technology Co., LTD.

检测报告

Inspection report



JB-NHJC-2016-A-177



福建南环检测技术有限公司



2013137017U

有效期至2016年08月27日

检测报告

第1页 共9页

检测专用章

检测项目		检测标准	检测结果	判定	备注
1. 外观检查					
1.1 表面质量					
1.1.1 表面缺陷	划痕	GB/T 10018.1-2005	0.2	合格	
	凹坑	GB/T 10018.1-2005	0.2	合格	
	气泡	GB/T 10018.1-2005	0.2	合格	
	杂质	GB/T 10018.1-2005	0.2	合格	
1.2 尺寸公差					
1.2.1 长度	总长	GB/T 10018.1-2005	1.000	合格	
	分节长	GB/T 10018.1-2005	0.250	合格	
	节间长	GB/T 10018.1-2005	0.250	合格	
	节宽	GB/T 10018.1-2005	0.250	合格	
1.3 力学性能					
1.3.1 拉伸强度	屈服强度	GB/T 10018.1-2005	10.0	合格	
	抗拉强度	GB/T 10018.1-2005	10.0	合格	
	伸长率	GB/T 10018.1-2005	10.0	合格	
	断面收缩率	GB/T 10018.1-2005	10.0	合格	
1.4 热性能					
1.4.1 热稳定性	热收缩率	GB/T 10018.1-2005	0.2	合格	
	热膨胀率	GB/T 10018.1-2005	0.2	合格	
	热变形温度	GB/T 10018.1-2005	0.2	合格	
	热分解温度	GB/T 10018.1-2005	0.2	合格	
1.5 电性能					
1.5.1 绝缘电阻	体积电阻率	GB/T 10018.1-2005	1.000	合格	
	表面电阻率	GB/T 10018.1-2005	1.000	合格	
	绝缘电阻	GB/T 10018.1-2005	1.000	合格	
	绝缘电阻	GB/T 10018.1-2005	1.000	合格	
1.6 其他性能					
1.6.1 耐候性	耐候性	GB/T 10018.1-2005	0.2	合格	
	耐候性	GB/T 10018.1-2005	0.2	合格	
	耐候性	GB/T 10018.1-2005	0.2	合格	
	耐候性	GB/T 10018.1-2005	0.2	合格	
1.7 其他性能					
1.7.1 其他性能	其他性能	GB/T 10018.1-2005	0.2	合格	
	其他性能	GB/T 10018.1-2005	0.2	合格	
	其他性能	GB/T 10018.1-2005	0.2	合格	
	其他性能	GB/T 10018.1-2005	0.2	合格	

右组外环境检测数据表

采样日期	采样点位	检测项目	采样日期: 2016 年 05 月 13 日				评价	达标
			1	2	3	均值	标准值	情况
		风速 Us (m/s)						
		标准风量 (m³/s)						

有组织废气检测结果表 5

采样点位	检测项目	采样日期: 2016年05月13日				评价标准值	达标情况
		1	2	3	均值		
6#包装机 N 24°44'58.05" E 116°11'18.75" 烟囱高度 20m	烟温 t (℃)	42	42	42	42	/	/
	含湿量 Xsw (%)	2.8	2.8	2.8	2.8	/	/
	风速 Us (m/s)	22.2	21.7	19.7	21.2	/	/
	标态风量 (m³/h)	22184	21748	19680	21204	/	/
粉尘	实测浓度 (mg/m³)	3.1	2.0	5.5	3.5	20	达标
	排放速率 (kg/h)	0.069	0.043	0.108	0.075	/	/
1#水泥磨 N 24°45'12.25" E 116°11'23.36" 烟囱高度 25m	烟温 t (℃)	95	96	96	96	/	/
	含湿量 Xsw (%)	2.9	2.9	2.9	2.9	/	/
	风速 Us (m/s)	6.0	6.8	7.5	6.8	/	/
2#水泥磨 N 24°45'12.16" E 116°11'23.36" 烟囱高度 25m	排放速率 (kg/h)	0.070	0.050	0.027	0.051	/	/
	烟温 t (℃)	84	85	84	84	/	/
	含湿量 Xsw (%)	3.4	3.4	3.4	3.4	/	/
	风速 Us (m/s)	7.9	8.6	9.1	8.5	/	/
	标态风量 (m³/h)	26418	28755	30431	28535	/	/
	粉尘	实测浓度 (mg/m³)	8.2	7.1	8.5	7.9	20
排放速率 (kg/h)		0.217	0.203	0.260	0.226	/	/



废水检测结果表

样品名称	采样日期：2016 年 05 月 13 日			
	pH	COD _{Cr} (mg/L)	NH ₃ -N (mg/L)	TTP (mg/L)
废水	7.47	15	0.038	0.01
评价标准值	6-9	100	15	/
评价结果	达标	达标	达标	/

备注: 1、N 24°45'23.50" E 116°11'22.98"

检测日期: 2023年04月13日		LeqdB (A)			
1#厂界西 N 24°45'16.51" E 116°11'07.85"	14:50~15:50	工业噪声	70.8	75	达标
	22:00~22:01	工业噪声	38.5	55	达标
	2#厂界东	14:50~14:51	工业噪声	58.3	65
2#厂界北 N 24°45'15.30" E 116°11'08.82"	14:50~15:50	工业噪声	70.8	75	达标
2#厂界北 N 24°45'20.70" E 116°11'10.70"	14:50~15:50	工业噪声	70.2	65	达标
2#厂界东 N 24°45'20.70" E 116°11'10.70"	14:50~15:50	工业噪声	70.2	65	达标

